



## TECHNICAL SHEET – WAX FOR INJECTION



## UNIVERSAL



### Characteristics:

- ✚ COLOR : PINK
- ✚ TEMPERATURE OF INJECTION : 65-68,5°C
- ✚ SOFT – WITH MEMORY – INJECTION AT LOW TEMPERATURE

### Advantages:

- ✚ SHINING SURFACE
- ✚ THE INJECTION AT LOW TEMPERATURE AVOIDS AIR BUBBLES
- ✚ EASY TO WORK BECAUSE OF THE GREAT FLEXIBILITY
- ✚ RECOMMENDED FOR STONE SETTING IN WAX

## MECAWAX



### Characteristics:

- ✚ COLOR : BEIGE
- ✚ TEMPERATURE OF INJECTION : 68-72°C
- ✚ NONE DEFORMATION ON THE WAX PIECES
- ✚ VERY LOW SHRINKAGE

### Advantages:

- ✚ USED FOR ALL PRODUCTION,
- ✚ AND SPECIALY FOR FLAT OR BIG PIECES

## BUL'O



### Characteristics:

- ✚ COLOR : PURPLE
- ✚ TEMPERATURE OF INJECTION : 64-68°C
- ✚ CHARACTERISTIC : SPECIAL FOR HIGH PRECISION CASTING AND FILIGREES

### Advantages:

- ✚ EASY MOLD REMOVAL WITHOUT DISTORSION
- ✚ BUILT IN MOLD RELEASE AGENT
- ✚ VERY SHINING SURFACE ON PATTERNS
- ✚ FLEXIBLE
- ✚ LOW SHRINKAGE 0,5 %
- ✚ BUILT WITH AN ANTI EMULSION AGENT
- ✚ NO RESIDUAL RESIDUES

## NATURAL



### Characteristics:

- ✚ COLOR : YELLOW
- ✚ Very SMOOTH AND BRIGHT SURFACE
- ✚ MINIMUM SHRINKAGE
- ✚ INJECTED AT HIGH TEMPERATURE: 72°C

### Advantages:

- ✚ NO ASH CONTENT
- ✚ SPECIALLY FORMULATED FOR FLAT OR HEAVY OBJECTS
- ✚ THE FLOW PROPERTIES MAKE IT
- ✚ IDEAL FOR THIN, LIGHTWEIGHT PIECES (FILIGREE)

## BIOWAX



### Characteristics:

- ✚ GREEN COLOR (FOR SUMMER FORMULA)
- ✚ HIGH CRYSTALLISATION POINT
- ✚ QUICK SOLIDIFICATION
- ✚ RIGID
- ✚ HIGH FLUIDITY
- ✚ LOW SHRINKAGE

### Advantages:

- ✚ SUITABLE FOR BOTH LARGE ITEMS AS WELL AS THE FINEST FILIGREE PATTERNS.
- ✚ ACCURATE REPRODUCTION OF FLAT SURFACES BECAUSE OF RAPID SOLIDIFICATION.
- ✚ GOOD MOULD RELEASE AS A RESULT OF HIGH STRENGTH AND FLEXIBILITY.